

CUT-OUT UNIT FOR UPTO 3 x 16mm² 4c SWA Cable


Order Code - TYPE 4/GCC

Dimensions

H - 337mm

W - 90mm

D - 93mm



SPD's are available
upon request



MCB's are available
upon request, please
confirm current rating
& short circuit rating



BWL & CW Cable
Glands are available
on request



Fuse Carriers are
available upon request



4 x TB033 blocks fitted

H - 38mm; W - 12mm; D - 52mm

4 x TB033C blocks fitted


H - 44mm; W - 12mm; D - 52mm

SPECIFICATION

- Street Lighting Cut-Out Unit
- Space for up to 4 x single pole MCB's or Fuse Carriers and Fuses.
- State MCB's rating & short circuit capacity at time of order
- Earth & Shrouded Neutral block for outgoing lantern cable
- Moulded in flame retardant material
- Hinged lockable lid
- All mouldings are secured by M4 stainless steel captive fixing screws into brass inserts
- Terminal blocks for up to 25mm loop in / loop out 4c cable
- Brass gland plate with 3 x 25mm holes & earth stud/lug kit
- BWL & CW cable glands can be supplied please confirm size & quantity at time of Order
- IP44 Rated - tested and certified by NAREC - ASTA certified Test Laboratory

CUT-OUT UNIT FOR UPTO 3 x 16mm² 4c SWA Cable

Order Code - TYPE 4/GCC



DIMENSIONS:

H - 337mm

W - 90mm

D - 93mm

